













# PRODUCT DATA CLICK MODA PLANK RIGID CORE

PRODUCT			
Click LVT Rigid core SPC+ EVA	EN ISO 10582		IBRIDO MODA
Locking System			Click 14F
Classification	EN ISO 10874		23/31
SPECIFICATION			
Thickness	EN ISO 24337		5mm
Weight	EN ISO 24342		8.64kg/m <sup>2</sup>
Wear Layer	EN ISO 24346		0.3mm
PRODUCT PROPERTIES			
PROPERTY	TEST METHOD		RESULT
Impact sound reduction	EN ISO 717-2:2013		19ΔLw (dB) (IXPE underlayment)
Indoor air certifications			Floorscore, A+, GreenGuard
Abrasion resistance	ASTM D3 884		AC3
Staining	EN 438-2		Pass (Grade 5)
Underfloor heating			OK (max+27°C)
Recycling			Suitable
Fire resistance	EN 13501-1		Bfl-s1
Residual indentation	EN ISO 24343-1		0.2mm
Slip resistance	EN 13893 / DIN 51130		R10
Phthalate free			Yes
Click MODA Plank	168 x 1220 x 5mm / 2.46m <sup>2</sup> per box		
Warranty	<b>RESIDENTIAL:</b> 15 years <b>LIGHT COMMERCIAL:</b> 7 years		

**CE**  
EN 14041

